

EcoCatalyst™ is a powerful, highly concentrated bio-organic catalyst formulated to provide a catalytic broad-spectrum agent for use within wastewater treatment facilities, sludge handling and dewatering facilities, residuals stations and collection systems.

EcoCatalyst™ rapidly solubilizes fats, greases, biofilms and slime layers, providing the optimum conditions for maintaining aerobic biology. Increases dissolved oxygen (DO) levels and improves waste stream utilization by the heterotropic microorganisms as a nutrient source.

EcoCatalyst™ provides an immediate and substantial reduction of the strongest odors, including hydrogen sulfides (H²S), and will eliminate the conditions that produce odors.



EcoCatalyst™

INDUSTRIAL STRENGTH Bio-Organic Catalyst

**Rapid Solubilization of
Fats, Oils & Grease (FOG)**

**Elimination of Hazardous
Gases and Noxious Odors**

**Increases Dissolved Oxygen
in Sewers, Lagoons &
Aeration Tanks**

Bacteria Free

1 gallon 5 gallon 55 gallon

U.S. Patent No 5,885,950

DIRECTIONS FOR USE

Metered Pumps

One (1) ppm, or lower, of EcoCatalyst™, in high-flow collection systems, and in higher concentrations under low-flow conditions (i.e. 1,000,000 x 1)

Power Washers / Hoses

One (1) ounce of EcoCatalyst™ to one (1) gallon of water (i.e. 128 x 1).

Hand Sprayers / Water Buckets

One (1) ounce of EcoCatalyst™ to one-half (1/2) gallon of water (i.e. 64 x 1).

EcoCatalyst™ is non-toxic, noncaustic, hypoallergenic and safe to handle with a recommended shelf life of two years. May be stored with confidence at temperatures below 125°F / 50°C. Keep out of the reach of children. If product splashes in eyes, rinse with water.

Contents: Biocatalysts, biosurfactants, organic stabilizers and minerals.

A Product of:
Bio-Organic Catalyst, Inc.
Costa Mesa, CA 92627